

Microwaves & RF

2000 EDITORIAL INDEX

COMMERCIAL

- New distributor aims at RF and fiber solutions (March, p. 40)
- Distribution group adds value to industry (August, p. 40)
- Global group provides extensive design services (August, p. 170)

COMMUNICATIONS

- Wireless up-and-comers head for the spotlight (April, p. 29)
- Fiber-optic link connects 10-GHz signals (April, p. 133)
- Antenna technology tunes to wireless markets (May, p. 31)
- Refining CDMA mobile-phone power control (May, p. 71)
- Bluetooth meets WLANs—can they live together? (August, p. 31)
- Turbulence muddies the telecom waters (December, p. 29)

COMPONENTS

- Design a logamp RF pulse detector (January, p. 62)
- Extend DDS bandwidth above the Nyquist limit (January, p. 82)
- Develop a trimless voltage-controlled oscillator (January, p. 94)
- Virtual LO tunes direct-conversion receivers (January, p. 107)
- Balance trade-offs in GaAs FET LNAs (February, p. 55)
- Achieve phasor rotation with analog switches (February, p. 59)
- Directional detector chip monitors wireless handsets (February, p. 65)
- Power dividers hold tight tolerances (February, p. 136)
- Attenuators combine speed and bandwidth (February, p. 138)

- Digital predistortion linearizes CDMA LDMOS amps (March, p. 55)
- Design an antenna for pacemaker communication (March, p. 73)
- Reviewing the basics of microstrip lines (March, p. 79)
- Extend DDS bandwidth above the Nyquist limit (March, p. 97)
- InGaP amplifier targets wireless applications (March, p. 156)
- HBT power amplifier serves CDMA needs (April, p. 72)
- Design waveguide bandpass filters (April, p. 93)
- Details count in power-amplifier design (April, p. 105)
- OCXOs shrink in size and power consumption (April, p. 140)
- Multicarrier power amplifier boosts cellular signals (April, p. 146)
- Simulate and build a Ku-band DRO (May, p. 103)
- Update the design of image-parameter filters (May, p. 119)
- Predict total losses in amplifier-matching networks (May, p. 130)
- RF notch filters are programmable (May, p. 207)
- SMT phase shifters adjust PCS designs (May, p. 210)
- Instant programming customizes oscillators (May, p. 216)
- Advancing the analysis of microwave oscillators (June, p. 55)
- Model and build a Ku-band DRO (June, p. 85)
- Couplers shrink HF/VHF/UHF designs (June, p. 93)
- Multilayer technology delivers high-performance miniature components (June Cover, p. 131)
- Phase-locked DRO achieves low noise and cost at 26 GHz (June, p. 144)
- LDMOS device powers WCDMA amplifier (June, p. 150)
- Design a Ka-band integrated microstrip isolator (July, p. 68)
- Roll rings offer stable electrical coupling (July, p. 110)

2000

EDITORIAL INDEX

- Four-port circulator drops into PCS systems (July, p. 112)
- Analyze VCOs and fractional-N synthesizers (August, p. 57)
- Modulation schemes affect the linearity of an HBT amp (August, p. 80)
- Digital predistortion linearizes RF PAs (August, p. 95)
- Determine IMD products for digitally modulated communication standards (August, p. 137)
- FBAR technology shrinks CDMA handset duplexers (August, p. 71)
- Design regular and irregular-print coupled lines (September, p. 97)
- Create technology line matching circuits for power amplifiers (September, p. 109)
- Control circuit compensates error loop in feedforward amplifiers (September, p. 120)
- HBT amplifiers boast high linearity (September, p. 148)
- Dielectric resonators offer broad tuning ranges (September, p. 153)
- Filter-based subsystem switches from 1 to 18.5 GHz (September, p. 154)
- BWOs tune across millimeter-wave applications (September, p. 156)
- SDLVAs detect high-speed pulsed signals (September, p. 158)
- Devise a millimeter-wave PHEMT mixer (October, p. 56)
- Biphasic modulators serve wireless and radar systems (October, p. 75)
- Create transmission-line matching circuits for power amplifiers (October, p. 113)
- Space switch transfers 140-W power at S-band (October Cover, p. 135)
- Module combines switches and amps for 5-GHz WLANs (October, p. 154)
- Precision SMA pads operate from DC to 18 GHz (October, p. 158)
- S-band amplifier modeled for wireless data (November, p. 53)
- Defining and testing dynamic ADC parameters (November, p. 75)
- Simulate PLL performance through direct digital synthesis (November, p. 87)
- Devise a GMSK modulator using the power of DSP (November, p. 109)
- Linear amplifiers provide power for telecom use (November, p. 152)
- Embedded antenna simplifies integration in WLAN devices (November, p. 154)
- Check amplifier dynamic behavior with true test signal (December, p. 47)
- Calculate the effect of RF building blocks on AM and PM noise (December, p. 56)
- Gunn oscillator attains W-band operation with GaAs diode (December, p. 65)
- Simplified method eases the design of bandpass filter (December, p. 97)
- Choosing terrestrial microwave antennas for extreme environments (December, p. 115)
- Novel FET mixers balance dynamic range and power consumption (December Cover, p. 167)
- Multichannel PA boosts cellular signals (December, p. 181)
- Model, analyze, and simulate fractional-N synthesizers (December, p. 183)
- DC block provides high-voltage protection through 50 GHz (December, p. 208)

COMPUTER-AIDED ENGINEERING

- Math software is ready for the millennium (January, p. 136)
- Model PLL dynamics and phase-noise performance (February, p. 73)
- Software tames engineering drawings (February, p. 134)
- Webwatch section (March, p. 111)
- Webwatch section (April, p. 121)
- Create a supercomputer for design and optimization (May, p. 80)
- Model PLL dynamics and phase-noise performance (May, p. 88)
- Accurately compute PLL active-filter parameters (June, p. 78)
- EM-based models improve circuit simulators (June, p. 97)
- Software simplifies physical modeling (June, p. 113)
- CD-ROM contains powerful analysis tools (June, p. 116)
- SPICE program sweetened with features (June, p. 119)
- System-design tool augments model libraries (June, p. 122)
- Math program adds functions, toolboxes (June, p. 124)
- Signal-processing packs extend math software (June, p. 126)
- Predict NPR for RF modules using system simulation (July, p. 55)
- Mathematical recipe calculates the response of dipole antennas (September, p. 51)
- Webwatch section (October, p. 125)
- Latest EDA software adds wireless features (December,

2000

EDITORIAL INDEX

p. 153)

- Software tames data analysis (December, p. 156)
- Linear simulator hones performance (December, p. 158)
- Software simulates comm systems (December, p. 160)
- CD-ROM encyclopedia sorts global radars (December, p. 162)

CONFERENCES

- Wireless Symposium heralds innovations (March, p. 31)
- 2000 International Microwave Symposium (May, p. 150)
- MTT-S products (May, p. 192)
- Educational choices abound at ninth Wireless Symposium (December, p. 125)
- Broad mix slated for the Wireless Symposium (December, p. 144)

CROSSTALK

- Eugene Brannock, executive vice president of marketing and engineering for Fujitsu Compound Semiconductor, Inc. (July, p. 37)

DEFENSE ELECTRONICS

- Defense spending choices force a balancing act (June, p. 29)
- Frequency synthesizer spans 2 to 18 GHz in 10-MHz steps (October, p. 150)

DEVICES & ICS

- High-speed GaAs ICs network at 10 Gb/s (January, p. 132)
- Transceiver ICs advance Bluetooth applications (January, p. 138)
- Chip solutions aim at low-cost WLANs (February, p. 108)
- InGaP/GaAs provides high-linearity HBTs (February, p. 121)
- TDMA receiver ICs serve PCS (February, p. 140)
- GaAs MMIC switch is designed around low-capacitance MESFETs (March, p. 93)
- Bluetooth integration poses challenges for developers (May, p. 55)
- Analyze IC integrations at the system level (May, p. 67)
- Stable IC controls amplifier power (May, p. 212)
- Transceiver chip targets PWC (May, p. 214)
- Multiplexer/demultiplexer ICs cut SONET power and cost (May, p. 220)
- GaAs FETs offer improved specifications (June, p. 160)

- Use transmitting power FETs for antenna switching (July, p. 81)
- High-power transistor boosts aircraft radar (July, p. 114)
- Digital upconverter IC tames complex modulation (August Cover, p. 159)
- ICs help implement a trim-free VCO (August, p. 172)
- Vacuum electronics are alive and well at the NRL (September, p. 31)
- Biasing N-channel GaAs MESFETs (September, p. 81)
- RF ICs serve handsets and base stations (September, p. 160)
- Understanding thermal basics for microwave power devices (October, p. 101)
- IEDM offers first glimpse of future devices (November, p. 29)
- Power devices stake their territories (November, p. 125)
- CMOS yields high-speed 5-GHz WLAN chip set (November, p. 156)
- Transmitter and receiver ICs run on ISM and SRD bands (December, p. 196)
- Broadband fixed wireless transceiver serves UNII band (December, p. 200)
- Error-correction ICs bolster wireless Internet access (December, p. 202)
- Crystal-clock oscillator reaches new supply low (December, p. 204)

MATERIALS

- Wireless semi technology heads into new territory (February, p. 31)
- Thick-film fabrication yields thin-film performance (February, p. 97)
- InGaP/GaAs provides high-linearity HBTs (February Cover, p. 121)
- New materials make microwave components safer for users (September, p. 62)
- Aluminum nitride forges high-power resistive components (September Cover, p. 135)
- SiGe's influence spreads to many applications (October, p. 29)

SYSTEMS & SUBSYSTEMS

- Studying biomedical issues of high-frequency radiation (February, p. 105)
- Microwave synthesizer meets demanding communications requirements (March, p. 63)
- Dual digital receiver commands 70-dB range (March, p. 154)

2000

EDITORIAL INDEX

- Enhance GMSK performance with two-point modulation (April, p. 59)
- Macro applications seen for micro radar (May, p. 39)
- Calculate intercept and compression points (May, p. 141)
- Refining CDMA mobile-phone power control (June, p. 71)
- Integrated RF synthesizer conserves space and power (June, p. 158)
- Optical systems look to 10 Gb/s and beyond (July, p. 29)
- Increase CDMA network capacity with a transmit combiner (July, p. 66)
- DSPs cut power and add cellular channels (July, p. 118)
- Modeling systems based on Bluetooth wireless connectivity (August, p. 121)
- Gauging the effects of nuclear radiation on microstrip antennas in space (August, p. 145)
- Bluetooth enables line of wireless sensors (September, p. 150)
- GaAs MMICs power high-frequency communications systems (October, p. 148)
- Design a frequency synthesizer for mobile communications systems (November, p. 63)

TEST & MEASUREMENT

- Mobile-phone test sets take aim at a moving target (January, p. 29)
- Measure harmonics with a spectrum analyzer (January, p. 55)
- NIST unveils status of PIM testing (January, p. 72)
- Comparing on-wafer cal techniques to 110 GHz (January, p. 114)
- Instrument emulates cable-network impairments (January Cover, p. 124)
- Signal analyzer checks transmitters to 10 Gb/s (January, p. 134)
- Increase throughput with confidence interval testing (February, p. 85)
- Noise generator checks high-data-rate satcom (February, p. 131)
- Field-strength analyzer undergoes upgrade (February, p. 142)
- VNA-based system tests differential components (March Cover, p. 126)
- Prematching tuners advance load-pull testing (March, p. 139)
- Switch cards fit compact VXI format (March, p. 152)
- Making EMI-radiated emissions measurements (April,

- p. 49)
- Fine-tuning test methods for CDMAOne handsets (April, p. 84)
- Measurement receiver speeds signal-generator calibration (April, p. 144)
- Vector signal analyzers augment test bandwidths (April, p. 148)
- Test system evaluates broadband distortion (April, p. 150)
- Automated preselector filter streamlines CATV testing (April, p. 152)
- Analyzer adds speed and accuracy to NF testing (May Cover, p. 199)
- Scopes test mixed analog and digital designs (May, p. 218)
- VXI synthesizer sports wideband modulation (June, p. 140)
- Digital modulation forces new testing techniques (July, p. 89)
- Line stretchers ease VCO load-pull testing (July Cover, p. 107)
- Multipurpose analyzers tackle group-delay tests (July, p. 116)
- Measure INL and DNL for high-speed ADCs (August, p. 109)
- VNAs set new marks for noise, speed, and automation (September, p. 140)
- Solving a high-frequency signal-integrity problem (October, p. 63)
- Measuring power levels in modern communications systems (October, p. 89)
- Meters and sensors simplify power tests on complex waveforms (October, p. 142)
- Scopes offer high bandwidth and time-saving features (October, p. 146)
- Measure gain of power RF/microwave transistors (November, p. 117)
- Spectrum analyzers tune to new levels of test performance (November Cover, p. 137)
- Vector modulator forms digital generators from analog sources (November, p. 146)
- Communications analyzer boasts versatility and high bandwidth (November, p. 150)
- Evaluate the shielding effectiveness of flexible coaxial cables (December, p. 69)
- Measuring and evaluating dynamic ADC parameters (December, p. 78)
- Perform precise microwave measurements (December, p. 101)

